



Material Safety Data Sheet

Date Originated: 25/03/2010

Page: 1

NFPA 	HCS Risk Phrases	Protective Clothing 
	HCS CLASS: Toxic. HCS CLASS: Irritating substance. HCS CLASS: Target organ effects. HCS CLASS: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F).	

Section 1. Chemical Product and Company Identification

Product Name

MC-Thinner 100

Synonym

W43.0

Manufacturer

SUPPLIER:
 Wasser Corporation
 4118 B PL NW, Suite B
 Auburn, WA 98001, US
 Phone# 253-850-2967

Chemical Family

Not available (Paint thinner).

In case of Emergency

EMERGENCY PHONE NUMBERS:
 USA and Canada: 1-800 424-9300
 International: 1-703 527-3887

Section 2. Composition and Information on Ingredients

Name	CAS #	% by Weight	TLV/PEL	LC ₅₀ /LD ₅₀
Light aromatic solvent naphtha (petroleum)	64742-95-6	60-100	TWA: 50 (ppm) from ACGIH (TLV)	ORAL (LD50): Acute: 6960 mg/kg [Rat]. DERMAL (LD50): Acute: 4000 mg/kg [Rabbit]. VAPOR (LC50): Acute: 10200 ppm 4 hour(s) [Rat].
Methyl n-amyl ketone	110-43-0	10-30	TWA: 50 (ppm) from ACGIH (TLV) TWA: 100 (ppm) from OSHA (PEL)	ORAL (LD50): Acute: 1670 mg/kg [Rat]. DERMAL (LD50): Acute: 12600 mg/kg [Rabbit]. VAPOR (LC50): Acute: 3000 ppm 4 hour(s) [Rat].

Material Safety Data Sheet

Product Name: MC-Thinner 100

Page: 2

Section 3. Hazards Identification

Routes of Entry: Inhalation. Skin contact (absorption). Eye contact. Ingestion.

Potential Acute Health Effects

Eyes: Liquid or spray mist may severely irritate eyes. Inflammation of the eye is characterized by redness, watering, and itching.

Skin: This product may irritate skin upon contact. Harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Ingestion: Harmful if swallowed. Irritation or chemical burns of the mouth, pharynx, esophagus and stomach can develop following ingestion of this product. Even small amounts of liquid aspirated into the lungs during ingestion or vomiting may cause pulmonary injury and possibly death.

Inhalation: Harmful if inhaled (irritant). Over-exposure by inhalation of the vapors/spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Exposure can cause nausea, headaches and vomiting. Severe overexposure can cause unconsciousness and death.

Potential Chronic Health Effects

Eyes: Repeated or prolonged contact with spray mist may produce chronic eye irritation.

Skin: Repeated skin exposure can produce local skin destruction, or dermatitis.

Ingestion: May be fatal if swallowed.

Inhalation: Repeated or prolonged inhalation of vapors/spray mist may lead to chronic respiratory irritation.

Other chronic effects on Humans

The substance is toxic to mucous membranes, upper respiratory tract, lungs, blood, kidney, liver. Exposure may cause asthma, dermatitis and pulmonary oedema; effects may be delayed.

Section 4. First Aid Measures

Eye Contact Check for and remove any contact lenses. IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. DO NOT use an eye ointment. Seek medical attention.

Skin Contact Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Rinse with plenty of running water (15 to 30 minutes). If irritation persists, seek medical attention.

Hazardous Skin Contact If the chemical gets onto the clothed portion of the body, remove the contaminated clothes as quickly as possible, protecting your own hands and body. Place the person under shower. Wash gently and thoroughly the contaminated skin with running water and non abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Rinse with plenty of running water (15 to 30 minutes). Seek medical attention.

Inhalation Allow the person to rest in a well ventilated area. If symptoms persist, seek medical advice immediately (show the label when possible).

Hazardous Inhalation Evacuate the person to a safe area as soon as possible. Loosen tight clothing around the person's neck and waist. If the person is not breathing, administer mouth-to-mouth resuscitation. WARNING: It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation if the inhaled material is toxic, infectious or corrosive. Oxygen may be administered if breathing is difficult. Seek medical attention.

Ingestion DO NOT induce vomiting. Have conscious person drink several glasses of water or milk. Seek immediate medical attention.

Hazardous Ingestion DO NOT induce vomiting. Have conscious person drink several glasses of water or milk. Never give an unconscious person anything to ingest. Even small amounts of liquid aspirated into lungs during ingestion or from vomiting may cause mild to severe pulmonary injury and possibly death. If breathing is difficult, administer oxygen. If the person is not breathing, administer mouth-to-mouth resuscitation. WARNING: It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation when the material is toxic, infectious or corrosive. Avoid mouth-to-mouth contact by using mouth guards or shields. Seek immediate medical attention.


Material Safety Data Sheet

Product Name: MC-Thinner 100

Page: 3

Section 5. Fire and Explosion Data

Flammability of the Product	Combustible.
Auto-Ignition Temperature	The lowest known value is 393°C (739.4°F) (Methyl n -amyl ketone).
Flash Points	The lowest known value is CLOSED CUP: 39°C (102.2°F). (Tagliabue.). (Methyl n-amyl ketone)
Flammable Limits	The greatest known range is LOWER: 1.1% UPPER: 7.9% (Methyl n-amyl ketone)
Products of Combustion	Carbon oxides (CO, CO2), and other unidentified, possibly toxic compounds.
Fire Hazards in Presence of Various Substances	Combustible in presence of open flames and sparks.
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Possible.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemicals, CO2, water spray or foam. LARGE FIRE: Use water spray or fog. Never direct a water jet in the container in order to prevent any splashing of the product which could cause spreading of the fire. Cool the containers with water spray or fog in order to prevent pressure build-up, autoignition or explosion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. When heated to decomposition it emits toxic fumes. Liquid will float and may reignite on surface of water.
Special Remarks on Explosion Hazards	Container explosion may occur under fire conditions or when heated (due to pressure build-up). Vapor forms explosive mixture with air between upper and lower flammable limits.



Section 6. Accidental Release Measures

Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal. Wear suitable protective clothing and proper respirator.
Large Spill	Combustible, poisonous liquid, insoluble or very slightly soluble in water. Ventilate. Eliminate all sources of ignition. Wear full protective equipment, including respiratory equipment during clean-up. Stop leak if without risk. DO NOT touch spilled material. Prevent entry into storm or sanitary sewers, lakes, rivers, streams or public waterways. Call for assistance on disposal.

Material Safety Data Sheet

Product Name: MC-Thinner 100

Page: 4

Section 7. Handling and Storage

Precautions	Keep locked up and out of reach of children. Manipulate in a well ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Do not breathe gas/fumes/vapor/spray. Avoid contact with skin and eyes. Contact lenses should not be worn when working with chemicals because they may contribute to the severity of an eye injury. Keep away from foodstuff, drinks and tobacco. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Ensure that eyewash station and safety shower is proximal to the work-station location. In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible). Individuals with respiratory problems (asthma, chronic bronchitis), or allergic to solvents, should avoid any contact with this product. Ground all equipment containing material (during handling, mixing and spraying).
Storage	Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed and in a well-ventilated place. Keep away from incompatibles. A refrigerated room would be preferable for materials with a flash point lower than 37.8°C (100°F).

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash station and safety shower are close to the work-station location.
Personal Protection	Splash goggles. Full suit. Gloves (impervious). In case of insufficient ventilation, wear suitable respiratory equipment. During spray application: Air-purifying respirator with an organic vapor cartridge and particulate pre-filters. Be sure to use a MSHA/NIOSH approved respirator or equivalent.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves (impervious). A self contained breathing apparatus should be used to avoid inhalation of the product.

Section 9. Physical and Chemical Properties

Physical state and appearance	Liquid.	Odor	Aromatic.
Molecular Weight	Not applicable.	Taste	Not available.
pH (1% soln/water)	Not applicable.	Color	Colorless.
Boiling Point	The lowest known value is 152°C (305.6°F) (Methyl n-amyl ketone). Weighted average: 153.54°C (308.4°F)	Odor Threshold	The highest known value is 0.05 ppm (Methyl n-amyl ketone)
Melting Point	May start to solidify at -35.5°C (-31.9°F) based on data for: Methyl n-amyl ketone.	Evaporation rate	0.4 (Methyl n-amyl ketone).compared to Butyl acetate = 1
Critical Temperature	Not available.	Viscosity	Not available.
Specific Gravity	0.86 (Water = 1)	Water/Oil Dist. Coeff.	Not available.
Vapor Pressure	The highest known value is 2.1 mm of Hg (@ 20°C) (Methyl n-amyl ketone). Weighted average: 2.02 mm of Hg (@ 20°C)	Ionicity (in Water)	Not available.
Vapor Density	The highest known value is 4.3 (Air = 1) (Light aromatic solvent naphtha (petroleum)). Weighted average: 4.22 (Air = 1)	Dispersion Properties	Is not dispersed in water.
Volatility	Volatile.	Solubility	Insoluble in water.

Section 10. Stability and Reactivity Data

Stability	The product is stable.
Instability Temperature	Not available.
Conditions of Instability	No additional remarks.
Incompatibility with various substances	Reactive with strong oxidizing agents.
Corrosivity	Not considered to be corrosive for glass and metals according to our data base.
Special Remarks on Reactivity	No additional remarks.

Material Safety Data Sheet

Product Name: MC-Thinner 100

Page: 5

Section 11. Toxicological Information

Routes of Entry	Inhalation. Skin contact (absorption). Eye contact. Ingestion.
Toxicity to Animals	See: Section 2
Chronic Effects on Humans	The substance is toxic to mucous membranes, upper respiratory tract, lungs, blood, kidney, liver. Exposure may cause asthma, dermatitis and pulmonary oedema; effects may be delayed.
Other Toxic Effects on Humans	Dangerous in case of skin contact (irritant, permeator), of eye contact (irritant), of ingestion, of inhalation.
Special Remarks on Toxicity to Animals	No additional remark.
Special Remarks on Chronic Effects on Humans	Narcotic effect; may cause nervous system disturbances. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage, and other systemic effects. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.
Special Remarks on other Toxic Effects on Humans	Material is irritating to mucous membranes and upper respiratory tract. Exposure can cause nausea, headache and vomiting. May be aggravating to some skin and asthma-type conditions, and to pre-existing liver/or kidney disorders.

Section 12. Ecological Information

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Products of Biodegradation	Not available.
Toxicity of the Products of Biodegradation	Not available.
Special Remarks on the Products of Biodegradation	No additional remarks.

Section 13. Disposal Considerations

Waste Disposal	In accordance with municipal, state and federal regulations. Consult your local or regional authorities. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.
----------------	---

Section 14. Transport Information

DOT Classification	DOT CLASS 3: Flammable liquid with a flash point greater than 37.8°C (100°F). PG: III
DOT Identification number	UN1263 Paint related material.
Special Provisions for Transport	No additional remarks.
DOT (Pictograms)	



Material Safety Data Sheet

Product Name: MC-Thinner 100

Page: 6

Section 15. Other Regulatory Information and Pictograms

Other Regulations TSCA (Toxic Substance Control Act): All components of this product are either reported in EPA TSCA Inventory, or exempt. OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications WHMIS (Canada)

DSCL (EEC)

Hazardous Material Information System (U.S.A.)

Health Hazard	2
Fire Hazard	2
Reactivity	0
Personal Protection	X

National Fire Protection Association (U.S.A.)

Health



Fire Hazard

Reactivity

Specific hazard

WHMIS (Canada) (Pictograms)

DSCL (Europe) (Pictograms)

TDG (Canada) (Pictograms)

ADR (Europe) (Pictograms)

Protective Clothing (Pictograms)



Section 16. Other Information

References Manufacturer's MSDS, RTESC, NIOSH, CCOHS.

Other Special Considerations Individuals with respiratory problems (asthma, chronic bronchitis) should avoid any contact with this product.

Validated by HS Reg.Depart.Reg.SS on 25/03/2010.

Verified by HS Reg.Depart.Reg.SS.

Printed 25/03/2010.

EMERGENCY PHONE NUMBERS:

USA and Canada: 1-800 424-9300

International: 1-703 527-3887

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.